

## LUMINAIRE STYLE

N - Non-Decorative / Non-Shrouded  
 S - Solid Spun Top / Shrouded / Side Mount  
 W - Solid Spun Top and Struts  
 T - Tenon  
 P - Pendant  
 2 - Two struts (580 series)  
 3 - Three struts (580 series)  
 4 - Four struts (580 series)


## IES LIGHTING CLASSIFICATION

2X - Type II (P4)  
 3X - Type III (B2, T1, P4)  
 4X - Type IV (B3, R1, T1, P4)  
 5X - Type V (B2, B3, R1, T1, P4)

### WATTAGE

025 - 25W  
 040 - 40 W  
 060 - 60 W  
 075 - 75 W  
 100 - 100 W  
 120 - 120 W  
 150 - 150 W  
 200 - 200 W

## LUMINAIRE SERIES



## SHIELD AND EMITTER

### OPTICAL OPTIONS

B3 - B3 Optic (Baffled Array)  
 R1 - R1 Optic (Refractive Array)  
 T1 - T1 Optic (Tower Array)  
 P4 - P4 Optic (Flat Array)

### CCT

30 - 3000K  
 40 - 4000K

### LENS OPTIONS

AR - Acrylic Rippled / Acrylic Refractor (K400 acorns)  
 AC - Acrylic Clear  
 AF - Acrylic Frosted  
 PR - Polycarbonate Rippled / Polycarbonate Refractor (K400 acorns)  
 PC - Polycarbonate Clear  
 GR - Glass Refractor (K400 acorns)  
 AV - Acrylic Vertical Prisms (K423)  
 NG - No Globe (K137)  
 NL - No Lens (lanterns, octagonal)  
 FL - Flat Lens (no lens pendant)  
 SA - Sag Lens (Clear Glass)  
 SH - Shallow Lens (Clear Glass)  
 AD - Acrylic Deep Dish  
 GD - Glass Deep Dish  
 TD - Tear Drop (K841)  
 GS - Rippled Glass Shallow (K200 series)  
 AS - Acrylic Shallow Refractive (K200 series)  
 PS - Polycarbonate Shallow Refractive (K200 series)  
 AW - Acrylic White (KG series)  
 PW - Polycarbonate White (KG series)